

DAMP PROOF EXTERIOR COATING

Upto
08 year
water-proofing
warranty.

Upto
10 Degree
celsius surface
temperature reduction.

- It is made from elastomeric emulsion with acrylic fiber.
- Rajyog damp proof coating provides thick and durable water-proof membrane.
- It is made from quality elastomeric polymers which provide long lasting water-proofing.
- Waterproofing warranty upto 08 years on vertical and horizontal walls.
- It provides crack bridging benefits due to elastomeric emulsion
- It reduces surface temperature up to 10 degree celsius during afternoon



Direction For Use

- New plasters should be allowed to dry for minimum of 30 days
- Surfaces should be clean from dust, grease and loose paints before coating.
- If required use Jet spray machine or vaccum cleaners to clean surface thoroughly.
- Fill cracks upto 3 mm by Rajyog Crack Seal. Fill bigger cracks with cement mortars.
- Do not apply Coatings during rains or high temperatures.
- Apply coatings on parapet walls also for better results.

Application Process

Vertical Walls

- Apply 1st coat of Rajyog Damproof diluted with water in the ratio of 3:1
- Apply 2nd coat of Rajyog Damproof without dilution

Coverage

Vertical Surface New Painting Surface Re-painting Surface	2.25 Sq.mtr - 2.25 Sq.mtr/ltr 2.25 Sq.mtr - 2.75 Sq.mtr/ltr
Horizontal Surface	0.8 - 10 Sq.mtr/ltr

Areas of Application



Exterior vertical walls



Building roofs



Terrace

Pack Available In



1 ltr.



4 ltr.



10 ltr.



20 ltr.

Horizontal Walls

- Apply 1st coat of Rajyog Damproof diluted with water in the ratio of 3:1
- Apply 2 perpendicular coats of Rajyog Damproof coating without dilution of water.
- Apply coating on complete terrace surface including parapet walls.

Precaution: Do not apply coating when raining or high temperature.

Shelf Life: Best before 36 month from Mfg.